

# **CORDLESS POWER TOOL CHARGERS**

#### Fit for both Ni-Cd / Ni-MH & Li-ion Power Tool Batteries



pecinications			
Model	ACMT	ACMG	ACME
nnut	100-240V / 1.24 MAX		

\* Fit for Ni-Cd/Ni-MH & Li-ion Power Tool Batteries

7.2V - 18V / 3A MAX.

- \* Interchangeable plates to suit different battery models, simply change the charger plates
- \* Cover 90% Power Tool battery models

# **CORDLESS POWER TOOL BATTERIES**

We provide compatible power tool battery packs for a wide range of brands available in market: Makita, Milwaukee, Worx, Greenworks, DeWalt, Bosch, Ryobi, Paslode, Panasonic, Hitachi, AEG, Black & Decker, Craftsman, Firestorm, National, and Skil,

21.6V - 36V / 2.1A MAX







\*All brands, trademarks and registered trademarks are the property of their respective holders.







7.2V - 18V / 1.5A MAX.





<sup>\*</sup>All brands, trademarks and registered trademarks are the property of their respective holders.

# **BATTERY CELLS**

Battery cells of different capacity available YLE manufactures high quality Li-NMC cells which can be used in the making of battery packs for eBikes, LED Lightings, Household Appliances and many other devices.

Nominal Voltage

Typical Capacity

Chemistry

Chemistry

Chemistry

Nominal Voltage

Typical Capacity

Nominal Voltage

Typical Capacity

Continuous Current

Continuous Current

Nominal Voltage

Typical Capacity

Continuous Current

Nominal Voltage

Typical Capacity

Continuous Current

Continuous Current

NCR10370D45 A

Li-NCA

3.6V

450mAh

Li-NCΔ

3.6V

2100mAh

4A

Li-NCA

3.6V

1600mAh

5A

NCR18500A260 A

Li-NCA

2600mAh

2.6A

Li-NMC

2000mAh

Li-NCA

3.6V

3600mAh

3.6V

20A

3.6V



Nominal Voltage

Typical Capacity

Chemistry

Chemistry

Chemistry

Chemistry

Nominal Voltage

Typical Capacity

Continuous Current 22A

Nominal Voltage

Typical Capacity

Continuous Current

Nominal Voltage

Typical Capacity

Continuous Current

Nominal Voltage

Typical Capacity

Continuous Current

Continuous Current

NCR14430A115 A

Li-NCA

3.6V

1150mAh

2.5A

NCR16300D95 A

Li-NCA

3.6V

3A

950mAh

NCR18350A160 A

Li-NCA

3.6V

1600mAh

3A

NCR18620 33 D3

Li-NCA

3300mAh

Li-NMC

2500mAh

3.6V

3.6V

7A

# DIGITAL CAMERA & VIDEO CAMCORDER BATTERY PACKS & CHARGERS

#### **BATTERY PACKS**







Voltage: 7.2V Capacity: 2250mAh



Fit model: Canon

Voltage: 7.4V

Capacity: 750mAh



Voltage: 3.7V Capacity: 980mAh

Voltage: 7.2V Capacity: 2250mAh

Voltage: 7.2V Capacity: 700, 800mAh







Voltage: 3.7V




Voltage: 7.4V



Voltage: 3.85V Capacity: 620mAh Capacity: 1200mAh Capacity: 920mAh Capacity: 1440mAh Capacity: 1300mAh Capacity: 1100mAh

**NEW PRODUCT** We supply battery packs for digital cameras and camcorders equipped with Type-C charging interfaces.

Voltage: 7.2V





**USB Dual Charge** 

Output: DC 4.2V / 8.4V 0.6A\*2





**AVEQ Series** 

For 3.6~4.2V

Specifications:

Input: DC 5V / 1A

Output: DC 4.2V / 1A

Dimension: 79 x 47 x 22mm



Fit model: Canon Fit model: Fujifilm Fit model: Pansonic

Voltage: 7.4V Voltage: 7.2V Voltage: 7.2V Capacity: 1050mAh Capacity: 2280mAh Capacity: 7400mAh Capacity: 970mAh Capacity: 1940mAh Capacity: 1940mAh

**ACMPB Series** 

Output: DC 4.2V / 8.4V

Dimensions: 80 v 48 v 28mm

Specifications: Input: 100 - 240V; 50 / 60Hz

**BATTERY CHARGERS** 

Specifications:

AVMP Series

Charger DC Output: DC 4.2V/8.4V

Input: 100 - 240V: 50 / 60Hz

Output: DC 12V / 1A







# Dimension: 85 x 54 x 23mm **USB Charger For**



\*All brands, trademarks and registered trademarks are the property of their respective holders.

## **POWER BANK**



**EL1906** Fully charge the batteries within 2 hours with PD140W input

66840 / 69600mAh | MAX. 290W | DC, USB-A, USB-C High Power | DC, USB-A, USB-C LCD Smart Display | UPS Function



# **UNIVERSAL LAPTOP AC & TYPE C ADAPTERS**

We provide 38 kinds of Interchangeable connector tip for customers to choose with.

Select a suitable connector tip and fit into the laptop DC-in jack tightly and steadily. Then connect the DC output of the Power Adapters.



















65W USB-C Charger 100W USB-C Charger



Input: 100 - 240V / Max 2.2A USB-C1/C2 Output: 5.0V=3.0A, 9.0V=3.0A, 12.0V=3.0A, 15.0V=3A, 20.0V=5.0A(100.0W Max) USB-A Output: QC30W Max

Input: 100 - 240V / Max 1.5A Output: 5.0V-3.0A/9.0V-3.0A/12.0V-3.0A/15.0V-3.0A /20.0V-3.25A 65W Max

\*All brands, trademarks and registered trademarks are the property of their respective holders.

# DIVERSIFIED LAPTOP COMPUTER BATTERIES



#### \*All brands, trademarks and registered trademarks are the property of their respective holders.

## BATTERY CELL WITH TYPE C CHARGING

Batteries are provided with reliable built-in safety Protection Circuit Modules (PCM) to protect against Over Charge, Over Discharge, Overload and Under Voltage

#### **Compatible AAA**









1.5V 800mAh 1200mWh 900mAh 1350mWh



**Compatible AA** 

1.5V 2760mAh 4140mWh 3480mAh 5220mWh



2760mAh 4140mWh 1.5V 3120mAh 4680mWh 3480mAh 5220mWh

#### **Compatible CR123**





**Compatible C** 

1.5V 3090mAh 4640mWh

#### **Compatible D**



# **E-BIKE BATTERY PACKS**















\*All brands, trademarks and registered trademarks are the property of their respective holders.

# **POWER TO** THE PORTABLE

# **PORTAPOWER** www.portapower.com



Scan the QR code to get the e-file

Flat 1003, 10/F., Hopeful Factory Centre, 10-16 Wo Shing St., Fotan, N.T., Hong Kong Tel: (852) 2687 6323 Fax: (852) 2687 6312

www.portapower.com